

Model number: PF450 / PF560

Description: Activair Portable fans

activair
Moving air since 1927

www.tombling.com

FEATURES:

- **Two diameters -**
PF450 - 450mm (18in.)
PF560 - 560mm (22in.)
- **Maximum output -**
PF450 - 5400m³/hr (3180CFM)
PF560 - 10800m³/hr (6360CFM)
- **Heavy duty metal casing and guards**
- **Corrosion proof epoxy finish - beige RAL7032**
- **Sealed maintenance free motor**
- **Locking tilt adjustment**
- **Speed control**
- **On-off switch**
- **4 metre lead**
- **Fitted 13A UK mains plug**
- **2 year guarantee**



MODEL	PF450	PF560
Fan diameter (mm)	450	560
Maximum airflow (m ³ /s)	1.5	3
Supply voltage (V)	230	230
Supply frequency (Hz)	50	50
Supply connection	13A UK mains plug	13A UK mains plug
Sound level (dBA)	63	69
Colour	RAL7032 beige	RAL7032 beige
Operating temperature (C)	-20 to +50	-20 to +50
Protection class	IP X4	IP X4
Weight (kg)	17	25
Width (mm)	671	791
Height (mm)	678	733
Depth (mm)	460	460

Activair portable cooling fans are designed for use with a standard UK 230V single phase 50Hz electrical supply.

They are suitable for use in most of Europe, Eastern Europe and the Middle East. However, please check your electrical supply is compatible before ordering.

Our policy is one of continuous improvement and development. Specifications can change at any time. Please contact sales for further information.

W. Tombling Ltd. 8 Broad Street, Spalding, Lincolnshire, PE11 1TB, United Kingdom
Tel. +44 (0) 1775 722948 Fax. +44 (0) 1775 724417 E-mail sales@tombling.com
Visit our website at: www.tombling.com